

This PDF is generated from: <https://www.aitesigns.co.za/Fri-30-Apr-2021-13626.html>

Title: Bc28 and base station communication log

Generated on: 2026-04-08 01:51:03

Copyright (C) 2026 AITESIGNS SOLAR. All rights reserved.

For the latest updates and more information, visit our website: <https://www.aitesigns.co.za>

-----

BC35-G& BC28 OpenCPU Series User Guide NB-IoT Module Series Rev. BC35-G& BC28-OpenCPU\_Series\_User\_Guide\_V1.0

This chapter introduces the error values related to BC35-G and BC28 modules. The error codes listed in the following two tables are ...

Contribute to LiteOS/LiteOS.github.io2 development by creating an account on GitHub.

1 Introduction This document gives details of the AT Command Set supported by Quectel NB-IoT BC35-G and BC28 modules. The following string will be output after booting the module: ...

DebugKits is a log capture tool that is used to capture the log of the BC68-GV and BC95-GV modules for further analysis when users encounter problems during debugging or using the ...

A decoder that leverages the message.xml file coming with the Quectel firmware to decode the debug log from the Quectel devices. - Quectel-debug-log ...

1 Introduction This document gives details of the AT Command Set supported by Quectel NB-IoT BC35-G, BC28 and BC95 R2.0 modules. The following string will be output after booting the ...

I've been told that BC28 based on Hisilicon platform can only enters PSM state (light sleep) by FAE. When the module enters PSM state, you can get response from UART.

I've been told that BC28 based on Hisilicon platform can only enters PSM state (light sleep) by FAE. When the module enters PSM ...

# Bc28 and base station communication log

Source: <https://www.aitesigns.co.za/Fri-30-Apr-2021-13626.html>

Website: <https://www.aitesigns.co.za>

View and Download Datalogic BC9180-BT quick reference manual online. Base Station/Charger. BC9180-BT base station pdf manual download.

This chapter introduces the error values related to BC35-G and BC28 modules. The error codes listed in the following two tables are compliant with the 3GPP specifications.

When the broadcast is sent, all properly configured scanners (Radio RX Timeout must be set to keep the radio "awake") that are linked to that base and within radio range coverage will emit a ...

Web: <https://www.aitesigns.co.za>

